



SPECIFICATION FOR APPROVAL

CUSTOMER :	DATE : 16-02-2008 DD/MM/YYYY	
CUSTOMER P/N :		
C.T.C. CH6080471K-542333-T P/N :	SAMPLEQ'TY :	
PRODUCT NAME : CH6080UTB-471K-018-VER00		
DRAWN BY:	CHECKED BY:	APPROVED BY:
Yu Xinze	Jiang Tianming	Tao Guowen

APPROVED BY CUSTOMER

	SIGNATURE	DATE
APPROVED		
CONDITIONAL APPROVED		
REJECTED		



C.T.C. Coils Limited 確力新實業有限公司

香港新界大埔汀角路 55 號太平工業中心 2 座 8 字樓 E 室
 Flat E, 8/F, Block 2, Tai Ping Ind. Centre, 55 Ting Kok Rd., Tai Po., N.T., Hong Kong
 Tel : (852) 2695-4889 Fax : (852) 2695-1842
<http://www.ctccoils.com> E-mail : enquiry@ctccoils.com


C.T.C. Electronics (Fonggang) Factory 東莞確力新電子廠

中國廣東省東莞市鳳崗鎮雁田區南山工業城第一棟
 Nanshan Industrial District, Yantian Village, Fenggang Town, Dongguan City,
 Guangdong Province, China, P.R.C.
 Tel : (86)769-7771591 Fax : (86)769-7771314

C.T.C. Electronics (Tangxia) Limited 東莞確一新電子有限公司

中國廣東省東莞市塘廈林村新太陽工業城第十七棟
 No.17, New Sun Industrial City, Tang Xia Town, Lin Cun, Dongguan City,
 Guangdong Province, China, P.R.C.
 Tel : (86)769-7811682 Fax : (86)769-7811382

SPECIFICATION FOR: () REF.:

C.T.C. P/N: CH6080471K-542333-T		DATE: 16-02-2008 DD/MM/YYYY			
PRODUCT NAME: CH6080UTB-471K-018-VER00					
1.DIMENSION (UNIT : mm):					
A: 11.0 Max.	B: 18.0 ± 0.5	C: 11.0 Max.	D: 9.0 ± 0.5	E: 0.65 ± 0.05	
F: 5.0+0.8/-0.5	G: 12.5 Min.	H: 18.0 +1.0/-0.5	I:	J:	
2.ELECTRIC CHARACTERISTICS: (TEST AT : 24°C ± 4°C)					
INDUCTANCE: 470 uH ± 10%		TEST FREQ: @1.0KHz/0.25V		DCR: 1.5 Ω Max.	
TURNS: 128.5 TS (Ref)		IDC: ---- A		RDC: 0.3 A	
Q: 25 Min. @ 0.796 MHz		SRF: 2.0MHz Min.		TEMP: -20°C ~ +80°C	
3.TEST EQUIPMENT:					
<input type="checkbox"/> HP-4284A (LCZ-METER)		<input type="checkbox"/> CH-1062 (LCZ-METER)		<input checked="" type="checkbox"/> CH-1320(CURRENT METER)	
<input type="checkbox"/> HP-8712C (ANALYZER)		<input type="checkbox"/> SK-3005 (INSULATION TESTER)		<input type="checkbox"/> MQ-1601 (Q-METER)	
<input checked="" type="checkbox"/> CH-100 (LCR-METER)		<input type="checkbox"/> CH-852A (HIGH POT TEST METER)		<input checked="" type="checkbox"/> HL-2801 (ANALYZER)	
<input checked="" type="checkbox"/> HK502BC (DCR-METER)		<input type="checkbox"/>		<input type="checkbox"/>	
4. MATERIALS: [2.0] [7]					
CORE: 02-B DR2W 6 X 8 (B:2.5 F:4.0 P:3.0)				PIN: CP	
WIRE: φ0.18mm 2 UEW 130°C			0.45 kg/kpcs		
SLEEVE: φ6 mm x 11 mm UL (MARK'G: CTC COLOR: BLUE) 11 m/kpcs					
VARNISH: ----			BOBBIN & BASE: -----		
COATING: ----		N.W: 1.13 kg/kpcs		PACKING: 1500PCS/BOX	
5.NOTE:					

DRAWN: Yu Xinze	CHECKED: Jiang Tianming	APPROVED: Tao Guowen
------------------------	--------------------------------	-----------------------------