

[Products](#) [Multimeter](#) [Digital handheld multimeter](#) [PeakTech® 2015](#)

PeakTech® 2015 PROD-ID: P 2015

[BACK](#)

Digital Multimeter ~ 4.000 Counts ~ 600V AC/DC ~ 10A AC/DC ~ Auto-Range

Newly developed Digital Multimeter, which is characterized by its ease of use, modern and handy design and the extensive measurement functions. Due to the high safety standard of overvoltage category CAT III 600 V and a large digital display with backlight this device is best suitable for the education-/service- and industrial area.

- 23 mm, 3 3/4-digit LCD display (max. 3999) with backlight and 41-segment-bargraph
- Auto and manual range selection
- MIN/MAX and Data-Hold
- Hz/Duty function and relative value
- Temperature measurement using type-K probe
- Fast continuity test and diode test
- Auto power off and low battery indication
- Safety: EN 61010-1; CAT III 600 V
- Accessories: holster, carrying case, test leads, Typ-K-thermocouple, battery and manual



MANUAL

[PeakTech 2015 02 2016.pdf \(556.5 kB\)](#)

PICTURES

[2015 Front Freigestellt.jpg \(1,979.3 kB\)](#)

[2015 L Freigestellt.jpg \(421.6 kB\)](#)

[2015 R Freigestellt.jpg \(493.1 kB\)](#)

DCV	40/400 mV/4/40/400/600 V; 10µV; +/- 0,5 % + 4 dgt.
ACV	40/400 mV/4/40/400/600 V; 10 µV; +/- 0,8 % + 6 dgt. Freq. Bereich: 40 ... 400 Hz
DCA	400 µA/4/40/400 mA/10 A; 0.1 µA; +/-1,0 % + 10 dgt.
ACA	400 µA/4/40/400 mA/10 A; 1 µA; +/- 1,5 % + 5 dgt. Freq.-Bereich: 40 ... 200 Hz
Ohm	400 Ω/4/40/400 kΩ/4/40 MΩ; 0,1 Ω; +/- 0,8 % + 4 dgt.
Capacitance	40/400 nF/4/40/400 µF; 10 pF; +/- 2,5 % + 8 dgt.
Frequency	100/1000 Hz/1/10/100 kHz/1/10 MHz; 0.1 Hz; +/- 0,5 % + 4 dgt.
Temperature	-20 ... +1000 °C; 1 °C; +/- 1,0 % + 4 dgt.
Operating voltage	9 V-Battery
Dimensions (WxHxD)	95 x 190 x 45 mm
Weight	400 g
EAN-13	4250569402364

